SONY

XM-SD46X

Amplifier

Key Features

- 600W max power
- 60W x 4 RMS into 4 ohms, 20Hz-20kHz @ 0.08% THD
- 60W x 2 + 150W x 1 RMS into 4 ohms, 20Hz-20kHz @ 0.1% THD
- 75W x 4 RMS into 2 ohms, 20Hz - 20kHz @ 0.1% THD
- Variable 50 ? 300Hz low/high pass filter
- 600W max power
- 60W x 4 RMS into 4 ohms, 20Hz-20kHz @ 0.08% THD
- 60W x 2 + 150W x 1 RMS into 4 ohms, 20Hz-20kHz @ 0.1% THD
- 75W x 4 RMS into 2 ohms, 20Hz - 20kHz @ 0.1% THD
- Variable 50 - 300 Hz low pass filter
- 40 Hz EQ boost
- MOSFET output stage & power supply
- RCA & speaker level inputs
- Line level thru-put
- CEA-2006 Power Compliant
- 2-Year limited warranty

Specifications

Audio

Frequency Response: 5-50k Hz

Input Level: 1.2-12V (Speaker level input)

Power

Power Consumption (in Operation): 600 Watts

Output Power: Bridged into 4 ohms, THD%- 60 x 2 + 150 x 1

Current Drain: 31A

Dimensions

Weight: 10 lbs, 6 oz (4.7 Kg)

Measurements: 11 x 2 1/4 x 15 7/8" (279 x 57 x 403mm)

UPC Code: 027242664791

SONY

XM-SD46X

Amplifier

Please visit the Dealer Network for more information at www.sony.com/dn

©2006 Sony Electronics Inc.
Reproduction in whole or in part without written permission is prohibited.
Sony is a trademark of Sony. All other trademarks are property of their respective owners.
Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.